

Declaration of Performance
for product Altrifloor BCP TG2 FSC Plywood 2440X1220X18MM
DOP-YZ-22-004-CE-18

1	Identification code :	FSC100% Plywood, NZ RADIATA PINE CORE, NZ RADIATA PINE F/B 2440*1220*18MM
2	Batch-/Serial number	
3	Intendent use:	Internal use as structural components in Humid condition
4	Harmonized technical specification	EN 13986:2004
6	System of Assessment and verification of constancy of performance (AVCP)	CE2+
7	Notified body:	APPLUS+
	Certificate N	0766-CPR-430/4

8 Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Bending strength parallel (N/mm ²)	58.3	ITT According to EN 310
perpendiculare (N/mm ²)	43.6	
Bending stiffness (Modulus Elasticity) parallel (N/mm ²)	5835	
perpendiculare (N/mm ²)	4860	
Classification according to EN636	F20/15 E40/25	EN636
Bonding quality	Class 2	ITT (EN314-1/2)
Durability (moisture resistance) (N/mm ²)	1,3	EN314-1/5.1.2
Moisture Content (Up to 14) (%)	14	EN 322
Density	550	EN 323
Release of Formaldehyde	E1	ISO 12460-3
Reaction to fire	Declared:D-s2,d0	

The performance of the product (products) is in conformity with the declared performance.
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufacturer by:

ZhangYe Quality Control Manager
(name and function)
Hegou Town OCT.18th, 2022
(place and date of issue)

ZhangYe *Quality Control Manager*

